Appln. No.: 10/552,989

## **IN THE CLAIMS**:

Please cancel Claims 1, 3-7, 15, 17 and 18 without prejudice or disclaimer of the subject matter recited therein.

Please amend Claims 16 and 19 and add new Claims 20-26 as follows.

1. to 15. (Cancelled)

16. (Currently Amended) [[A]] An electrophoretic display device according to claim 1, comprising:

a substrate;

a sealing plate;

a partition wall disposed between the substrate and the sealing plate;

a liquid layer, disposed in a container including the substrate and the partition wall, comprising electrophoretic particles and a dispersion medium;

a first electrode formed at a position apart from the partition wall on the substrate;

a second electrode formed along the partition wall; and

a resistance layer electrically connecting the first electrode and the second electrode and wherein the resistance layer comprises comprising an indium-tin-oxide film.

17. and 18. (Cancelled)

19. (Currently Amended) [[A]] An electrophoretic display device according to claim [[1]] 16, wherein the first electrode is formed of a metal film.

Appln. No.: 10/552,989

20. (New) An electrophoretic display device according to claim 16, wherein the resistance layer is continuously arranged between a surface of a liquid layer side of the first electrode and a surface of a liquid layer side of the second electrode.

- 21. (New) An electrophoretic display device according to claim 16, wherein the resistance layer is formed to cover the partition wall.
- 22. (New) An electrophoretic display device according to claim 16, wherein the resistance layer has a resistance value smaller than a resistance value of the liquid layer.
- 23. (New) An electrophoretic display device according to claim 16, further comprising an insulating layer disposed between the liquid layer and the first electrode and having a contact hole, wherein the first electrode and the second electrode are electrically connected through the contact hole.
- 24. (New) An electrophoretic display device according to claim 23, further comprising a light reflection layer disposed between the first electrode and the substrate.
- 25. (New) An electrophoretic display device according to claim 23, wherein the insulating layer is a coloring layer.
- 26. (New) An electrophoretic display device according to claim 24, wherein the light reflection layer is formed of an uneven portion.